

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 01.11.2010

Revision: 01.11.2010

1 Identification of the substance/preparation and of the company/undertaking

· Product details

· Trade name: Capalac Disbocolor 781 Acryl-Sprühlack sdm.

· Article number:

812483, 812484, 812485, 812486, 812487, 812488, 812489, 812490, 812491, 812492, 812493, 205583, 205569, 205545, 205521, 205514, 205491, 205477, 205460, 205446, 205439, 205606

· Application of the substance / the preparation *Lacquer*

· Manufacturer/Supplier:

CAPAROL Farben, Lacke, Bautenschutz GmbH

Roßdörfer Strasse 50

D-64372 Ober-Ramstadt

Tel.: +49 (0)6154 71-0

Fax : +49 (0)6154 71-1351

Internet: www.caparol.de

Neue Bundesländer

Tel.: 030 63946-252

Fax.: 030 63946-400

· Further information obtainable from:

Technische Beratung/Bereich Caparol:

Tel.: +49 (0)6154 71-1710

Fax : +49 (0)6154 71-1351

tech-auskunft@caparol.de

· Information in case of emergency: +49 (0)6154 71-202

2 Hazards identification

· Hazard description:



Xi Irritant

F+ Extremely flammable

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Warning! Pressurized container.

Has a narcotizing effect.

R 12 Extremely flammable.

R 36 Irritating to eyes.

R 66 Repeated exposure may cause skin dryness or cracking.

R 67 Vapours may cause drowsiness and dizziness.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C (e.g. in the car). Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Buildup of explosive mixtures possible without sufficient ventilation.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

· Chemical characterization

· Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 01.11.2010

Revision: 01.11.2010

Trade name: Capalac Disbocolor 781 Acryl-Sprühlack sdm.

(Contd. of page 1)

· Dangerous components:		
CAS: 123-86-4 EINECS: 204-658-1	<i>n</i> -butyl acetate R 10-66-67	25-50%
CAS: 67-64-1 EINECS: 200-662-2	acetone Xi, F; R 11-36-66-67	10-25%
CAS: 106-97-8 EINECS: 203-448-7	butane (containing < 0,1 % butadiene (203-450-8)) F+; R 12	10-25%
CAS: 74-98-6 EINECS: 200-827-9	propane F+; R 12	10-25%
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate Xi; R 10-36	≤ 2.5%
CAS: 64742-94-5 EINECS: 265-198-5	Solvent naphtha (petroleum), heavy arom. Xn; R 65-66-67	≤ 2.5%
CAS: 67-63-0 EINECS: 200-661-7	propan-2-ol Xi, F; R 11-36-67	≤ 2.5%
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. Xn, Xi, N; R 10-37-51/53-65-66-67	≤ 0.5%
CAS: 64742-82-1 EINECS: 265-185-4	Naphtha (petroleum), hydrodesulfurized heavy Xn, N; R 10-51/53-65-66-67	≤ 0.5%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First-aid measures

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.

5 Fire-fighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**
Water
Water with full jet
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

GB

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 01.11.2010

Revision: 01.11.2010

Trade name: Capalac Disbocolor 781 Acryl-Sprühlack sdm.

(Contd. of page 2)

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Do not seal receptacle gas tight.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

123-86-4 n-butyl acetate

WEL	Short-term value: 966 mg/m ³ , 200 ppm
	Long-term value: 724 mg/m ³ , 150 ppm

67-64-1 acetone

WEL	Short-term value: 3620 mg/m ³ , 1500 ppm
	Long-term value: 1210 mg/m ³ , 500 ppm

106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

WEL	Short-term value: 1810 mg/m ³ , 750 ppm
	Long-term value: 1450 mg/m ³ , 600 ppm
	Carc (if more than 0.1% of buta-1.3-diene)

108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm
	Long-term value: 274 mg/m ³ , 50 ppm
	Sk

67-63-0 propan-2-ol

WEL	Short-term value: 1250 mg/m ³ , 500 ppm
	Long-term value: 999 mg/m ³ , 400 ppm

- **Additional information:** The lists valid during the making were used as basis.

- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
Berührung mit den Augen vermeiden
- **Respiratory protection:** Not required.

(Contd. on page 4)

GB

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 01.11.2010

Revision: 01.11.2010

Trade name: Capalac Disbocolor 781 Acryl-Sprühlack sdm.

(Contd. of page 3)

- **Protection of hands:**

In case of contact with spray dust protective gloves made of butyl should be used (min. 0.4 mm thick), e.g. KCL Camatril, article no. 898 or similar products

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **General Information**

Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic

- **Change in condition**

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: Not applicable, as aerosol.

- **Flash point:** Not applicable, as aerosol.

- **Self-igniting:** Product is not selfigniting.

- **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

- **Explosion limits:**

Lower:	1.2 Vol %
Upper:	13.0 Vol %

- **Vapour pressure at 20°C:** 8300 hPa

- **Density at 20°C:** 0.82 g/cm³

- **Solubility in / Miscibility with**

water:	Not miscible or difficult to mix.
VOC-(EU)	737.8 g/l

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

- **Materials to be avoided:**

- **Dangerous reactions** No dangerous reactions known.

- **Dangerous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** Irritating effect.

- **Sensitization:** No sensitizing effects known.

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 01.11.2010

Revision: 01.11.2010

Trade name: Capalac Disbocolor 781 Acryl-Sprühlack sdm.

(Contd. of page 4)

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

· Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

· Product:

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
15 01 04	metallic packaging

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

14 Transport information

· Land transport ADR/RID (cross-border)



· ADR/RID class: 2 5F Gases.

· Danger code (Kemler): -

· UN-Number: 1950

· Packaging group: -

· Hazard label 2.1

· Description of goods: 1950 AEROSOLS

· Limited quantities (LQ) LQ2

· Tunnel restriction code D

· Maritime transport IMDG:



· IMDG Class: 2.1

· UN Number: 1950

· Label 2.1

· Packaging group: -

· EMS Number: F-D,S-U

· Marine pollutant: No

(Contd. on page 6)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 01.11.2010

Revision: 01.11.2010

Trade name: Capalac Disbocolor 781 Acryl-Sprühlack sdm.

(Contd. of page 5)

· **Proper shipping name:** AEROSOLS· **Air transport ICAO-TI and IATA-DGR:**

· **ICAO/IATA Class:** 2.1
 · **UN/ID Number:** 1950
 · **Label:** 2.1
 · **Packaging group:** -
 · **Proper shipping name:** AEROSOLS, flammable

15 Regulatory information

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**

Xi Irritant
F+ Extremely flammable

· **Risk phrases:**

12 Extremely flammable.
 36 Irritating to eyes.
 66 Repeated exposure may cause skin dryness or cracking.
 67 Vapours may cause drowsiness and dizziness.

· **Safety phrases:**

2 Keep out of the reach of children.
 16 Keep away from sources of ignition - No smoking.
 23 Do not breathe aerosol.
 24/25 Avoid contact with skin and eyes.
 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
 46 If swallowed, seek medical advice immediately and show this container or label.
 51 Use only in well-ventilated areas.

· **Special labelling of certain preparations:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C (e.g. in the car). Do not pierce or burn, even after use.
 Do not spray on a naked flame or any incandescent material.
 Buildup of explosive mixtures possible without sufficient ventilation.

· **Classification in accordance with Directive 75/324/EEC:** Extremely flammable· **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant R-phrases**

10 Flammable.
 11 Highly flammable.
 12 Extremely flammable.

(Contd. on page 7)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 01.11.2010

Revision: 01.11.2010

Trade name: Capalac Disbocolor 781 Acryl-Sprühlack sdm.

(Contd. of page 6)

- 36 Irritating to eyes.
- 37 Irritating to respiratory system.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

· Contact:

Anwendungstechnik / Produktsicherheit

Telefon: 0180 / 500 72 72*

*(0,14€/Min. aus dem deutschen Festnetz, ggfs. abweichende Preise aus dem Mobilfunknetz und dem europ. Ausland)

info@jwo.com

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

- * **Data compared to the previous version altered.** SDB - Änderung gültig ab Abfüllung am

GB