

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.09.2011

Version number 3

Revision: 20.09.2011



## 1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** Capalac Disboklar 782 farblos sdm.
- **Article number:** 812495, 205644
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Application of the substance / the preparation** Clear coating material, Varnish
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
CAPAROL Farben, Lacke, Bautenschutz GmbH  
Roßdörfer Strasse 50  
D-64372 Ober-Ramstadt  
Tel.: +49 (0)6154 71-0  
Fax : +49 (0)6154 71-1351  
Internet: [www.caparol.de](http://www.caparol.de)  
Neue Bundesländer  
Tel.: 030 63946-252  
Fax.: 030 63946-400
- **Further information obtainable from:**  
Technische Beratung/Bereich Caparol:  
Tel.: +49 (0)6154 71-1710  
Fax : +49 (0)6154 71-1351  
[tech-auskunft@caparol.de](mailto:tech-auskunft@caparol.de)
- **Emergency telephone number:** +49 (0)6154 71-202

## 2 Hazards identification

- **Classification of the substance or mixture**

---

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
-  Xi; Irritant  
 R36: Irritating to eyes.
-  F+; Extremely flammable  
 R12: Extremely flammable.
- R52/53-66-67: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.
- **Information concerning particular hazards for human and environment:**  
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.  
At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.  
Warning! Pressurized container.  
Has a narcotizing effect.
- **Classification system:**  
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

---

- **Label elements**
- **Labelling according to EU guidelines:**  
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- **Code letter and hazard designation of product:**



Xi Irritant  
F+ Extremely flammable

(Contd. on page 2)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 20.09.2011

Version number 3

Revision: 20.09.2011

Trade name: **Capalac Disboklar 782 farblos sdm.**

(Contd. of page 1)

**· Risk phrases:**

- 12 Extremely flammable.  
36 Irritating to eyes.  
52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
66 Repeated exposure may cause skin dryness or cracking.  
67 Vapours may cause drowsiness and dizziness.

**· Safety phrases:**

- 2 Keep out of the reach of children.  
16 Keep away from sources of ignition - No smoking.  
23 Do not breathe aerosol.  
24/25 Avoid contact with skin and eyes.  
29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
46 If swallowed, seek medical advice immediately and show this container or label.  
51 Use only in well-ventilated areas.

**· Special labelling of certain preparations:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C (e.g. in the car). Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Buildup of explosive mixtures possible without sufficient ventilation.

**· Classification in accordance with Directive 75/324/EEC: Extremely flammable****· Other hazards****· Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### 3 Composition/information on ingredients

**· Chemical characterization: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

**· Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2	acetone Xi R36; F R11 R66-67 Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	25-<50%
CAS: 106-97-8 EINECS: 203-448-7	butane (containing < 0,1 % butadiene (203-450-8)) F+ R12 Flam. Gas 1, H220; Press. Gas, H280	20-<25%
CAS: 74-98-6 EINECS: 200-827-9	propane F+ R12 Flam. Gas 1, H220; Press. Gas, H280	12.5<20%
CAS: 1330-20-7 EINECS: 215-535-7	xylene Xn R20/21; Xi R38 R10 Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	5-<10%
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate Xi R36 R10 Flam. Liq. 3, H226; Eye Irrit. 2, H319	5-<10%

(Contd. on page 3)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 20.09.2011

Version number 3

Revision: 20.09.2011

**Trade name: Capalac Disboklar 782 farblos sdm.**

(Contd. of page 2)

CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. Xn R65; Xi R37; N R51/53 R10-66-67 Asp. Tox. 1, H304	2.5-<5.0%
CAS: 100-41-4 EINECS: 202-849-4	ethylbenzene Xn R20; F R11 Flam. Liq. 2, H225; Acute Tox. 4, H332	<2.5%
CAS: 95-63-6 EINECS: 202-436-9	1,2,4-trimethylbenzene Xn R20; Xi R36/37/38; N R51/53 R10 Flam. Liq. 3, H226; Aquatic Chronic 2, H411; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	<2.5%
CAS: 108-67-8 EINECS: 203-604-4	mesitylene Xi R37; N R51/53 R10 Flam. Liq. 3, H226; Aquatic Chronic 2, H411; STOT SE 3, H335	<1.0%
CAS: 98-82-8 EINECS: 202-704-5	cumene Xn R65; Xi R37; N R51/53 R10 Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335	≤0.5%
CAS: 103-65-1 EINECS: 203-132-9	propylbenzene Xn R65; Xi R37; N R51/53 R10 Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335	≤0.5%

**· Additional information:**

The naphthas contain less than 0,1% benzene (Note P Annex 1 67/548 EU)  
For the wording of the listed risk phrases refer to section 16.

**4 First aid measures****· Description of first aid measures**

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.

**5 Firefighting measures**

- **Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**  
Water  
Water with full jet
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

**6 Accidental release measures**

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 20.09.2011

Version number 3

Revision: 20.09.2011

**Trade name: Capalac Disboklar 782 farblos sdm.**

(Contd. of page 3)

- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Open and handle receptacle with care.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep container tightly sealed.  
Do not seal receptacle gas tight.  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.

## \* 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

<b>67-64-1 acetone</b>	
WEL	Short-term value: 3620 mg/m <sup>3</sup> , 1500 ppm Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm
<b>106-97-8 butane (containing &lt; 0,1 % butadiene (203-450-8))</b>	
WEL	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
<b>74-98-6 propane</b>	
OEL	Short-term value: 3600 mg/m <sup>3</sup> , 2000 ppm Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
<b>1330-20-7 xylene</b>	
WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV

(Contd. on page 5)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 20.09.2011

Version number 3

Revision: 20.09.2011

Trade name: Capalac Disboklar 782 farblos sdm.

(Contd. of page 4)

**108-65-6 2-methoxy-1-methylethyl acetate**

WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 274 mg/m<sup>3</sup>, 50 ppm  
Sk

**100-41-4 ethylbenzene**

OEL Short-term value: 880 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 440 mg/m<sup>3</sup>, 100 ppm  
WEL Short-term value: 552 mg/m<sup>3</sup>, 125 ppm  
Long-term value: 441 mg/m<sup>3</sup>, 100 ppm

**95-63-6 1,2,4-trimethylbenzene**

WEL Long-term value: 125 mg/m<sup>3</sup>, 25 ppm  
ILV

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

-

· **Respiratory protection:** Not required.

· **Protection of hands:**

In case of contact with spray dust protective gloves made of butyl should be used (min. 0.4 mm thick), e.g. KCL Camatril, article no. 898 or similar products

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Aerosol

Colour: According to product specification

· **Odour:** Characteristic

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

· **Flash point:** Not applicable, as aerosol.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

Lower: 1.5 Vol %

Upper: 13.0 Vol %

· **Vapour pressure at 20°C:** 8300 hPa

· **Density at 20°C:** 0.9 g/cm<sup>3</sup>

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 20.09.2011

Version number 3

Revision: 20.09.2011

Trade name: Capalac Disboklar 782 farblos sdm.

(Contd. of page 5)

· **Solubility in / Miscibility with water:** Not miscible or difficult to mix.

· **Viscosity:**  
**Dynamic:** Not determined.  
**Kinematic:** Not determined.

· **Solvent content:**  
**VOC-(EU)** 791.8 g/l

### 10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

**67-64-1 acetone**

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

**1330-20-7 xylene**

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	500 mg/kg (rabbit)

**64742-95-6 Solvent naphtha (petroleum), light arom.**

Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

**95-63-6 1,2,4-trimethylbenzene**

Oral	LD50	5000 mg/kg (rat)
------	------	------------------

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

Irritant

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

### 12 Ecological information

- **Toxicity**
- **Acquatic toxicity:** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 20.09.2011

Version number 3

Revision: 20.09.2011

Trade name: *Capalac Disboklar 782 farblos sdm.*

(Contd. of page 6)

- **Additional ecological information:**
- **General notes:**  
Harmful to aquatic organisms  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
15 01 04	metallic packaging

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 2 5F Gases.
- **Danger code (Kemler):** -
- **UN-Number:** 1950
- **Packaging group:** -
- **Hazard label** 2.1
- **UN proper shipping name:** 1950 AEROSOLS
- **Limited quantities (LQ)** 1L
- **Tunnel restriction code** D

- **Maritime transport IMDG:**



- **IMDG Class:** 2.1
- **UN Number:** 1950
- **Label** 2.1
- **Packaging group:** -
- **EMS Number:** F-D,S-U
- **Marine pollutant:** No
- **Proper shipping name:** AEROSOLS

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 20.09.2011

Version number 3

Revision: 20.09.2011

Trade name: *Capalac Disboklar 782 farblos sdm.*

(Contd. of page 7)

· **Air transport ICAO-TI and IATA-DGR:**

- **ICAO/IATA Class:** 2.1
- **UN/ID Number:** 1950
- **Label:** 2.1
- **Packaging group:** -
- **Proper shipping name:** AEROSOLS, flammable

- **UN "Model Regulation":** UN1950, AEROSOLS, 2.1
- **Special precautions for user** Warning: Gases.

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Relevant phrases**

- H220 Extremely flammable gas.
  - H225 Highly flammable liquid and vapour.
  - H226 Flammable liquid and vapour.
  - H280 Contains gas under pressure; may explode if heated.
  - H304 May be fatal if swallowed and enters airways.
  - H312 Harmful in contact with skin.
  - H315 Causes skin irritation.
  - H319 Causes serious eye irritation.
  - H332 Harmful if inhaled.
  - H335 May cause respiratory irritation.
  - H336 May cause drowsiness or dizziness.
  - H411 Toxic to aquatic life with long lasting effects.
- 
- R10 Flammable.
  - R11 Highly flammable.
  - R12 Extremely flammable.
  - R20 Harmful by inhalation.
  - R20/21 Harmful by inhalation and in contact with skin.
  - R36 Irritating to eyes.
  - R36/37/38 Irritating to eyes, respiratory system and skin.
  - R37 Irritating to respiratory system.
  - R38 Irritating to skin.
  - R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
  - R65 Harmful: may cause lung damage if swallowed
  - R66 Repeated exposure may cause skin dryness or cracking.
  - R67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:** Abteilung Technik 0671/870-301· **Contact:**

Anwendungstechnik  
Anwendungstechnik / Produktsicherheit  
Telefon: 0180 / 51172631\*

(Contd. on page 9)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 20.09.2011

Version number 3

Revision: 20.09.2011

**Trade name: Capalac Disboklar 782 farblos sdm.**

(Contd. of page 8)

*\*(0,14€/Min. aus dem deutschen Festnetz, ggfs. abweichende Preise aus dem Mobilfunknetz und dem europ. Ausland)*

*info@jwo.com*

**· Abbreviations and acronyms:**

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*IMDG: International Maritime Code for Dangerous Goods*

*IATA: International Air Transport Association*

*IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)*

*ICAO: International Civil Aviation Organization*

*ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)*

*VOC: Volatile Organic Compounds (USA, EU)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

GB