

Capadur Parkett- und Siegellack

One-component, transparent sealer for parquet flooring, wooden & enamel surfaces. For interior use.



Product Description

Field of Application	For transparent sealing of wood and cork flooring in private living quarters. Also suitable for sealing enamels and glazes indoors.
Material Properties	<ul style="list-style-type: none"> ■ Water-thinnable. ■ One-component. ■ Highly hard-wearing. ■ Good filling capacity. ■ Quick-drying. ■ Highly elastic. ■ Resistant to conventional household cleaning agents. ■ Facilitates coating without lapping, even on large surfaces. ■ Suitable for kids toys according to DIN EN 71-3.
Material Base / Vehicle	One-component, water-thinnable polyurethane.
Packaging/Package Size	750 ml, 2.5 litres and 10 litres
Colours	Transparent
Gloss Level	High-gloss and silk-matt.
Storage	Cool, but frost-free. Packaging should be closed air-tight.
Technical Data	<ul style="list-style-type: none"> ■ Density: Approx. 1,0 g/cm³ ■ Solids content: Approx. 30% by weight

Application

Suitable Substrates	Wood flooring, parquet, oriented strand boards (OSB), stairs and other wooden surfaces, cork-layer flooring, prefinished floor (ready-to-lay parquet) and lacquered or glaze-treated surfaces. The substrate must be clean, sound, dry, and free from all substances that may prevent good adhesion. Do not use on water-soluble wood stain. Essential: Check existing coatings for adhesion and verify their compatibility by a trial coating on site.
Substrate Preparation	Clean and sandpaper the surface to be coated thoroughly. Grind away existing parquet varnish completely. Sandpaper the surface of existing enamel and glaze / scumble coatings, e.g. with a suitable scouring pad (abrasive web made of nonwoven material).



Method of Application

Application:

Stir up the material before use. For the first coat the material may be thinned max. 20% with tap water, if required. The enamel varnish is uniformly applied by brush, sealer brush or roller.

Apply 2 - 3 coats on untreated wooden substrates, depending on the absorbency. Apply 3 - 4 coats on OSB boards. Apply 1 finishing coat on prefinished floor (ready-to-lay parquet), laminates and lacquered surfaces.

Consumption

Approx. 100 - 150 ml/m² per coat, depending on surface texture and absorbency of the substrate.

Application Conditions

Min. 12°C for material, substrate and ambient air.

Drying/Drying Time

At 20°C and 65% relative humidity: Can be sandpapered (sanded) and recoated after approx. 12 hours. Ready for stress after approx. 24 - 36 hours. Initial cleaning with water and mild cleaning agent and laying of carpeting is allowed after 1 week.

Note

Cleaning and Care:

Clean Capadur Parkett- und SiegelLack with hair-broom or vacuum cleaner. Remove soiling by a wet cleaning floor cloth. A conventional household cleaning agent, suitable for synthetic flooring, can be added to the fountain solution (water for mopping up). Follow the instructions given by the manufacturer of cleaning agents.

Do not use scouring agents (soft scrub cleansers) and solvents. Areas subjected to extremely high dirt loads, e.g. halls, front doors, etc., should be provided with dust-capturing mats. Provide case legs with felt pads and use soft chair wheels. Ideally a protective base (pad) should be placed under office chairs.

Advice

Please Note (Status as at Date of Publication)

Keep out of reach of children. In case of contact with eyes, rinse immediately with plenty of water. Do not empty into drains, water courses or onto the ground. Further information: See Material Safety Data Sheets (MSDS).

Disposal

Materials and all related packaging must be disposed of in a safe way in accordance with the requirements of the local authorities. Particular attention should be made to removing wastage from site in compliance with standard construction site procedures. In Germany: Only completely emptied containers should be given for recycling. Dispose containers with residues of liquid material as remnants of water-based paints and dried material as hardened paints waste or via domestic waste.

EU limit value for the VOC content

of this product (category A/i): 140 g/l (2010). This product contains max. 140 g/l of VOC.

Giscode

W2

Customer Service Centre

Tel.: (+49) 0 61 54 / 71 17 10
 Fax: (+49) 0 61 54 / 71 17 11
 e-mail: kundenservicecenter@caparol.de

International Distribution: Please see www.caparol.com

Technical Information No. 186 · Issue: July 2011

All suggestions and application instructions herein are based on our latest technical experience. Due to the wide variety of individual project conditions, we cannot be held responsible for their content. These instructions do not release the purchaser/ applicator from his responsibility to determine the suitability of the product in consideration of the project characteristics. These instructions are to be considered void when a new edition is released. Our general conditions of sale and delivery in their latest edition apply. This document is a translation of our German Technical Information No. 186 · Capadur Parkett- und SiegelLack · Issued: January 2010

DAW International Business: **Deutsche Amphibolin-Werke von Robert Murjahn Stiftung & Co KG** · P.O.B. 1264 · D-64369 Ober-Ramstadt · Tel. +49 6154 71-1274
 Fax +49 6154 71-1264 · E-mail export@daw.de · Internet www.caparol.com