

Capadecor® VarioPutz

Multicoloured, matt, small flakes type coating. Suitable for highly efficient interior paint roller and spray application.



Product Description

Field of Application	Multicoloured, highly durable (hard-wearing) interior wall coating. Eminently suitable for application on interior surfaces in offices, halls, stairways, reception and living areas.
Product Properties	<ul style="list-style-type: none"> ■ Emission-minimised, solvent-free, unplasticized and AgBB tested. ■ Economic paint roller or spray application. ■ Excellently cleanable. ■ Resistant to mechanical stress. ■ Easily repairable. ■ Fire behaviour classification according to German standard DIN 4102: A2 nicht brennbar (non-combustible).
Product Base / Vehicle	Synthetic resin dispersion/emulsion
Packaging/Package Size	12.5 kg
Colours	Transparent binder with coloured paint flakes/chips.

Please Note: For each VarioPutz Design (type/pattern) one previously applied covering intermediate coat of tinted Putzgrund 610 is essential. The colour formula is available on the ColorExpress tinting machine - see tinting software, Collection "CD VarioPutz".

Design/Type:	No. of Colour:	Colour Name:
VarioPutz No. 13	VP No. 13	VP No. 13
VarioPutz No. 14	VP No. 14	VP No. 14
VarioPutz No. 19	VP No. 19	VP No. 19
VarioPutz No. 21	VP No. 21	VP No. 21
VarioPutz No. 23	VP No. 23	VP No. 23
VarioPutz No. 25	VP No. 25	VP No. 25
VarioPutz No. 27	VP No. 27	VP No. 27
VarioPutz No. 29	VP No. 29	VP No. 29
VarioPutz No. 30	VP No. 30	VP No. 30
VarioPutz No. 31*	VP No. 31	VP No. 31
VarioPutz No. 32*	VP No. 32	VP No. 32
VarioPutz No. 35*	VP No. 35	VP No. 35
VarioPutz No. 41*	VP No. 41	VP No. 41
VarioPutz No. 49*	VP No. 49	VP No. 49
VarioPutz No. 51*	VP No. 51	VP No. 51
VarioPutz No. 53	VP No. 53	VP No. 53
VarioPutz No. 55	VP No. 55	VP No. 55



	<p>Roller Application: Stir VarioPutz with a slow turning electric paddle mixer. Apply undiluted product generously and evenly, wet-on-wet using suitable and well prepared (soaked) paint roller, then spread crosswise. Allow to flash off for a sufficiently long time, then treat/wipe with soft brushes (e.g. oval brushes). Flash-off time varies depending on conditions on site: approx. 10 to 30 minutes. Roller application is highly advisable for inner corners and different component parts.</p> <p>Spray Application: Stir VarioPutz with a slow turning electric paddle mixer and apply undiluted product with suitable spraying equipment. Spray in slightly rotary motion and do not rework.</p>
Consumption	<p>Roller application: Approx. 350 g/m², determine the exact consumption by a trial coating.</p> <p>Spray application: Approx. 800 - 1100 g/m², determine the exact consumption by a trial coating.</p>
Application Conditions	Min. +8 °C for product, substrate and ambient air during application and drying. RH below 65 %.
Drying/Drying Time	At +20 °C and 65 % relative humidity surface-dry after 6 - 8 hours. Completely dry and ready for stress (loadable) after approx. 3 days. Lower temperatures and higher humidity extend the drying time.
Tools	<p>Suitable rollers: Use paint rollers with a pile height of 12 to 16 mm (e.g. Rotaplast Rotastreif 13 or Triplegold 12)</p> <p>Suitable spraying equipment: Hopper spray gun, nozzle: 4 - 5 mm, air pressure: 2.5 - 3.5 bar</p>
Tool Cleaning	Clean paint rollers and spraying equipment immediately after use with tap water.
Note	<p>Always use product of same batch, when applying on large (seamless) surfaces and apply in one go, in order to avoid lapping and colour variations.</p> <p>Due to the use of Caparol-Tiefgrund TB in the interiors, a typical solvent odour is released, hence proper ventilation must be provided during the application. Use non-aromatic, low-odour AmphiSilan-Putzfestiger in sensitive areas.</p> <p>Reworking gypsum filling compounds may cause swelling, blistering or flaking/spalling due to long lasting moisture exposure. Hence provide for fast drying by means of sufficient ventilation and temperature.</p> <p>In Germany: Follow Data Sheet No. 2 „Verspachtelung von Gipsplatten / Trowel application on Plasterboards“ issued by Bundesverband der Gips- und Gipsplattenindustrie / German association of Gypsum and Plasterboard Industry.</p>

Advice

German Certificates	<p>■ Non-combustibility A2 according to German standard DIN 4102</p>
Please Note (Status as at Date of Publication)	<p>Keep out of reach from children. Use P2 dust filter for grinding. Ensure good ventilation during use and drying. Do not eat, drink or smoke while using the paint. In case of contact with eyes or skin, immediately and thoroughly rinse with water. Do not allow product to enter drains, waterways or soil. Clean utensils immediately after use with soap and water. Do not inhale spray dust. Use dust collector A2/P2. For further information see Material Safety Data Sheet (MSDS).</p>
Disposal	<p>Materials and all related packaging must be disposed of in a safe way in accordance with the full requirements of the local authorities. Particular attention should be made to removing wastage from site in compliance with standard construction site procedures.</p> <p>In Germany: Dispose containers with residues of liquid product via waste collection point accepting old paints and enamels. Dispose dried/hardened product residues as construction site/demolition/ municipal or domestic waste.</p>
Product Code Paints and Enamels	M-DF02
Substances of Content - Declaration	Acrylic resin dispersion/emulsion, coloured pigments, mineral fillers, water, film forming agent, additives, preservative
Technical Assistance	<p>As it is impossible to list herein the wide variety of substrates and their specific problems, please request our technical assistance in case of queries.</p> <p>We will describe appropriate working methods, if a substrate not specified above is to be coated.</p>
Customer Service Centre	<p>Tel.: (+49) 0 61 54 / 71 17 10 Fax: (+49) 0 61 54 / 71 17 11 e-mail: kundenservicecenter@caparol.de</p> <p>International Distribution: Please see www.caparol.com</p>

Technical Information No. 868 · Issue: May 2012

All suggestions and application instructions herein are based on our latest technical experience. Due to the wide variety of individual project conditions, we cannot be held responsible for their content. These instructions do not release the purchaser/ applicator from his responsibility to determine the suitability of the product in consideration of the project characteristics. These instructions are to be considered void when a new edition is released. Our general conditions of sale and delivery in their latest edition apply. This document is a translation of our German Technical Information No. 868 · Capadecor®
VarioPutz · Issued: April 2012